

HEYsign banners FACE your space

Grasping attention with every format.

Application	Article	Coating	Weight	Tensile strength	Width	Indoor only	DIN 4102 B1	NF P 92-503ff	EN 13501-1	NFPA 701 Test	Cal Adm Code	DIN 75200	FTPC Part 7	ÖNORM B 3800	Solvent	UV	Latex	HP-cert	Opening %	Air permeability	Tranlucency	Weldable	
backlit	backlit light eco B1 Ref. H6006-0301	PVC	500 g/m ² 14.7 oz/yd ²	2900/2500 N/5 cm 331/286 lbf/inch	320/500 cm 126/197 inch	✓									✓	✓	✓				30%	✓	
	backlit light B1 Ref. H6005-0301	PVC	500 g/m ² 14.7 oz/yd ²	2900/2400 N/5 cm 331/274 lbf/inch	320/500 cm 126/197 inch	✓	B s2 d0								✓	✓	✓	✓			28%	✓	
	backlit matt B1/M2 Ref. H5505-0302	PVC	650 g/m ² 19.2 oz/yd ²	2900/2700 N/5 cm 331/308 lbf/inch	320/500 cm 126/197 inch	✓	M2	162							✓	✓	✓				30%	✓	
	heylight B1 Ref. H5500-0303	PVC	680 g/m ² 20.2 oz/yd ²	3400/3300 N/5 cm 388/377 lbf/inch	320/500 cm 126/197 inch	✓		162							✓	✓	✓				30%	✓	
frontlit	frontlit light eco Ref. H5022-0295	PVC	500 g/m ² 14.7 oz/yd ²	2800/2100 N/5 cm 320/240 lbf/inch	320/500 cm 126/197 inch						✓				✓	✓	✓					✓	
	frontlit light eco B1/M2 Ref. H6022-0295	PVC	500 g/m ² 14.7 oz/yd ²	2700/2200 N/5 cm 308/251 lbf/inch	320/500 cm 126/197 inch	✓	M2				✓				✓	✓	✓	✓				✓	
	frontlit eco B1/M1 Ref. H6025-0295	PVC	500 g/m ² 14.7 oz/yd ²	2600/2100 N/5 cm 297/240 lbf/inch	320/500 cm 126/197 inch	✓	M1	B s2 d0	1						✓	✓	✓	✓					✓
	frontlit light B1/M2 Ref. H5469-0295	PVC	500 g/m ² 14.7 oz/yd ²	2900/2300 N/5 cm 331/264 lbf/inch	320/500 cm 126/197 inch	✓	M2								✓	✓	✓	✓					✓
	frontlit light B1/M1 Ref. H6471-0295	PVC	475 g/m ² 14 oz/yd ²	2900/2400 N/5 cm 331/274 lbf/inch	320/500 cm 126/197 inch	✓	M1	B s2 d0	2			✓			✓	✓	✓	✓					✓
	soft plus B1 Ref. H6803-0292	PVC	350 g/m ² 10 oz/yd ²	1670/1220 N/5 cm 191/139 lbf/inch	320/500 cm 126/197 inch	✓			2	✓					✓	✓	✓	✓					✓
	soft blueback B1 Ref. H6803-B951	PVC	350 g/m ² 10 oz/yd ²	1700/1220 N/5 cm 194/139 lbf/inch	320/500 cm 126/197 inch	✓			2	✓					✓	✓	✓	✓					✓
mesh	mesh matt eco Ref. H5024-0297	PVC	340 g/m ² 10 oz/yd ²	2600/1600 N/5 cm 297/183 lbf/inch	320/500 cm 126/197 inch						✓				✓	✓	✓		15%	1400 l/m ³ /s		✓	
	mesh matt B1/M1 Ref. H5071-0297	PVC	340 g/m ² 10 oz/yd ²	2600/1600 N/5 cm 297/183 lbf/inch	320/500 cm 126/197 inch	✓	M1	B s3 d0							✓	✓	✓		15%	1400 l/m ³ /s		✓	
	mesh matt B1 Ref. H6071-0297	PVC	340 g/m ² 10 oz/yd ²	2600/1600 N/5 cm 297/183 lbf/inch	320/500 cm 126/197 inch	✓	M1	B s3 d0							✓	✓	✓		15%	1400 l/m ³ /s		✓	
blockout	blockout B1/M2 Ref. H3512-0026	PVC	760 g/m ² 22.4 oz/yd ²	2900/2500 N/5 cm 330/285 lbf/inch	320/500 cm 126/197 inch	✓	M2	B s2 d0	2						✓	✓	✓	✓				✓	
truck	vectaplan panama print Ref. H5551-0290	PVC	900 g/m ² 26.5 oz/yd ²	4400/4200 N/5 cm 502/480 lbf/inch	300/320 cm 118/126 inch						✓				✓	✓	✓					✓	
	vectaplan 9/9 print Ref. H5560-0292	PVC	680 g/m ² 20 oz/yd ²	3400/3200 N/5 cm 388/365 lbf/inch	250/300 cm 98.4/118 inch						✓				✓	✓	✓					✓	

FR norm DIN 75200 - 100 mm/min | 3.4 inch/min



Application	Article	Coating	Weight	Tensile strength	Width	PVC-free	DIN 4102 B1	NF P 92-503ff	EN 13501-1	NFPA 701 Test1	Solvent	UV	Dye-Sub Latex	HP-cert	OekoTex®	Thickness	Translucency	weldable	pre-shrunk	foldable	sewable		
backlit	digitex® luxor B1 Ref. H7810-5401	PU-acrylic	155 g/m ² 4.6 oz/yd ²	430/820 N/5 cm 49/94 lbf/inch	320/510 cm 126/200 inch	✓	✓	✓			✓	✓	✓			0,25mm	50%				✓		
frontlit	digitex® decoflex B1/M1 Ref. H7304-5501	treatment	215 g/m ² 6.3 oz/yd ²	350/1500 N/5 cm 40/171 lbf/inch	up to 505 cm up to 198.8 inch	✓	✓	M1	✓	✓		✓	✓	✓	✓					✓	✓	✓	
	digitex® decoflex premium B1/M1 Ref. H7335-5501	treatment	220 g/m ² 6.5 oz/yd ²	400/1750 N/5 cm 46/200 lbf/inch	up to 505 cm up to 198.8 inch	✓	✓	M1	✓	✓		✓	✓	✓						✓	✓	✓	
	digitex® decoflex display plus B1/M1 Ref. H7313-0295	PUR	235 g/m ² 6.9 oz/yd ²	350/1200 N/5 cm 40/137 lbf/inch	up to 500 cm up to 197 inch	✓	✓	M1	✓	✓	✓	✓	✓				0,41mm				✓	✓	
	digitex® superior B1/M1 Ref. H7835-5296	PU-acrylic	340 g/m ² 10 oz/yd ²	1600/4000 N/5 cm 183/457 lbf/inch	320/500 cm 126/197 inch	✓	✓	M1	✓	✓	✓	✓	✓	✓								✓	
blockout	digitex® decoflex nightfever B1 Ref. H7385-5975	acrylic	260 g/m ² 8 oz/yd ²	300/1000 N/5 cm 34/114 lbf/inch	up to 505 cm up to 198.8 inch	✓	✓	✓	✓	✓		✓	✓	✓			0,4mm				✓	✓	✓
	digitex® decoflex nightfever soft B1* Ref. H7386-5975	acrylic	260 g/m ² 8 oz/yd ²	300/1000 N/5 cm 34/114 lbf/inch	up to 505 cm up to 198.8 inch	✓	✓	✓	✓	✓		✓	✓	✓			0,4mm				✓	✓	✓
	digitex® decoflex whitenight B1* Ref. H7390-5126	PU	365 g/m ² 11 oz/yd ²	300/1200 N/5 cm 34/137 lbf/inch	up to 505 cm up to 198.8 inch	✓	✓	✓	✓	✓	✓	✓	d	✓			0,44mm	>1%			✓	✓	✓
	digitex® decoflex whitenight soft B1* Ref. H7395-5126	acrylic	280 g/m ² 8 oz/yd ²	350/450 N/5 cm 40/51 lbf/inch	up to 505 cm up to 198.8 inch	✓	✓	✓	✓	✓	✓	✓	d	✓			0,4mm	>1%			✓	✓	✓
	digitex® decoflex doubleface B1* Ref. H7480-5126	treatment	440 g/m ² 13oz/yd ²	950/1000 N/5 cm 108/126 lbf/inch	up to 505 cm up to 198.8 inch	✓	✓	✓	✓	✓	✓	✓	✓	✓			0,75mm	>1%			✓	✓	✓
Wall and ceiling coverings	ceilstar® premium B1/M1 Ref. H7401-5290	PU	290 g/m ² 8.5 oz/yd ²	350/1100 N/5 cm 40/126 lbf/inch	320/420/510 cm 126/165/201 inch	✓	✓	M1	✓	✓	✓	✓	✓								✓	✓	

NEW 2022

NEW 2022

ecotex® - Environmentally friendly textiles



PVC-free coating	Weight	Tensile strength	Tear resistance	Width	Properties	DIN 4102 B1	NFPA 701 Test 1	EN 13501-1	Latex	UV	Solvent	DyeSub	weldable	foldable	sewable	glueable	air permeability
outdoor	frontlit H7022-0295	270 g/m ² 8 oz/yd ²	2800/2450 N/5 cm 320/280 lbf/in	550/500 N 124/112 lbf	up to 500 cm up to 197 in	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	mesh* H7071-0295	180 g/m ² 5 oz/yd ²	2300/1400 N/5 cm 263/160 lbf/in	380/340 N 85/76 lbf	up to 500 cm up to 197 in	approx 15% opening value	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	1400/ m ² / sec
indoor	decoflex-R* H7344-5501	215 g/m ² 6.3 oz/yd ²	350/1500 N/5 cm 40/171 lbf/in		up to 505 cm up to 198.8 in	recycled yarns	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	

No liability is assumed for any errors, Misprints and errors excepted. Changes can be made at any time without prior notice. The product is subject to fluctuations.

* preliminary data | DyeSub print: d= direct | t= transfer | ✓ = both

