

# SIGNax White, High Opacity Rigid film 400µm

## Highlights

- >>> Ideal for Pop-up Walls, Pole Banners, Billboards, Display Systems
- >>> Printable with UV, Screen Printing

	Technical specification	Test Method
<b>Thickness</b>	400 µm	N/A
<b>Material</b>	PVC	N/A
<b>Colour</b>	White (code 935)	/
<b>Surface</b>	matt	/
<b>Thickness tolerance</b>	±5 %	OPV - 002
<b>Width tolerance</b>	± 2 %	OPV - 002
<b>Max. Shrinkage</b>	201 - 500 µ L: max. -8 C: max. +2	DIN 53377 140° / 1 min
<b>Density</b>	± 1,47 g/ cm <sup>2</sup>	MSZ EN ISO 1183-1: 2013A
<b>Vicat softening</b>	±76°C	DIN EN ISO 306
<b>Surface tension</b>	±34 dyne	DIN 53364/ ISO 8296
<b>Tensile strength</b>	Min. 40 MPa	MSZ EN ISO 527-1-2-3
<b>Tensile impact strength</b>	±600 KJ/m <sup>2</sup>	MSZ EN ISO 8256 : 2004 A
<b>Elongation at break</b>	Min 50 %	MSZ EN ISO 527 1-2-3
<b>Glueability</b>	With PVC adhesive	N/A

(The product specification specifies the minimum guaranteed values for the offered type of material in rated quality).