

# SIGNax Knitted Blackback Textile 250gsm

## Highlights

- >>> Ideal for backdrops, exhibition, displays, pop up
- >>> Printable with Dye-Sub Transfer, Dye-Sub Direct, UV

	Technical specification	Test Method
<b>weight</b>	250g/sq.m	ISO536
<b>Weave Method</b>	Woven	N/A
<b>Material</b>	Polyester	DIN 60001, ASTM D7641
<b>Opacity</b>	> 90%	ISO2471
<b>Whiteness</b>	170±10	ISO11475
<b>Colour</b>	L:93.0±2.0; a:0.0±2.0; b:0.0±2.0	N/A
<b>Gloss (60°)</b>	3±1	N/A
<b>Elasticity</b>	Warp:(4±2) % Weft:(3±2) %	Length*Width=200*50mm, Speed=100mm/min, Tension=20N
<b>Shrinkage</b>	≤3%	200°C, 45s
<b>Yellow ΔE</b>	≤2	200°C, 45s
<b>Recommended Fixation Temperature</b>	190-200°C, 45s	N/A
<b>Yellow Temperature</b>	≥210°C	SUPRKC REX-C400, 30S
<b>Flame Resistance</b>	DIN 4102-1-B1, NFPA 701 TEST1, EN13501-1	DIN 4102-1-B1, NFPA 701 TEST1, EN13501-1
<b>Width Available</b>	Max. 505 cm	DIN EN ISO 3759
<b>Standard Length</b>	50m / 100m	DIN EN ISO 3759

(The product specification specifies the minimum guaranteed values for the offered type of material in rated quality).