

JT 7501 WG-PB 40

PRODUCT DESCRIPTION

Polymeric perforated window film self adhesive printing media.

Face Material: 160 μm white gloss PVC with black reverse side, 1.5 mm perforation, 40% open area

Adhesive: Solvent acrylic transparent removable

Liner: 140 g/sqm PE coated liner + 55 g/sqm perforated paper

TYPICAL USE

Short to medium term indoor and outdoor promotional graphics on flat smooth glass surfaces on buildings and vehicle windows for advertising

PROCESSING

Especially designed for UV-curable inks, JT 7501 WG-PB 40 is also compatible for solvent based, ecosolvent, mild solvent and Latex inkjet printing on wide-format printing equipment.

To achieve optimal protection and durability, JT 7501 WG-PB 40 needs to be laminated with LUV 7036 or LF 10500 Series.

To achieve the best possible print quality, please make sure that the correct ICC profiles or printer settings are used.

Profiles can be obtained from our subsidiaries or distributors, or can be downloaded from: www.mactacgraphics.eu.

For further information on printing, application and removal, please refer to "TB 4.1 Guidelines on handling, converting and applying Mactac Digital media".

To ensure application suitability, always test the proposed construction under actual application and end-use conditions before going into full production.

SHELF LIFE

2 year when stored at 15 to 25°C and \pm 50 % relative humidity (in the original packaging).

PHYSICAL PROPERTIES (TYPICAL VALUES) Average Values Test Method

	AVC	lage ve	nacs	iest method		
Thickness						
Film + Adhesive (microns)	185 µm			ISO 534		
Adhesive data, 23°C (N/25 mm)						
Peel adhesion on stainless steel						
- 20 min.		5		FTM1		
- 24 hours	24 hours			FTM1		
Dimensional stability						
Shrinkage (1 week at 70°C applied on Aluminium)	Max. 0.3 mm			FTM14		
Temperature ranges						
Minimum application temperature (°C)			+ 10°C			
End-use (°C)			- 15°C to + 60°C			
Certifications						
Fire Classification	B-s1, d0			EN 13501-1		

EXPECTED DURABILITY

Central Europe Zone 1

Unprocessed	3 years	ISO 4892-2
Printed & laminated*	Up to 3 years	ISO 4892-2

*For more information, refer to "TB 7.5 Outdoor Durability of Mactac Graphics - Self-adhesive films".

Note : Overlamination of the inkjet-printed material delays the eventual colour fading that may occur over time. This colour fading is dependent on the quality of the inkjet inks, the orientation of the printed material, the angle of display and the exact geographical location of exposure.

Exposure to severe temperatures, ultraviolet light, and/or conditions in Southern European countries, tropical, sub-tropical or desert regions will cause more rapid deterioration. This also applies to polluted areas, high altitudes and south-facing exposure

DISCLAIMER

For more information on the durability and exposure please visit the "Mactac Technical Bulletin TB 7.5 Outdoor Durability of Mactac Graphics - Selfadhesive films" on the www.https://www.mactacgraphics.eu website.

Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see

http://terms.europe.averydennison.com. Avery

Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.

