

Think Sustainable!

All paper based packaging elements of our self-adhesive graphics products are 100% recyclable where appropriate paper waste recycling bins are available, and many are already made from recycled content, including inner cores, packaging boxes and plastic core stoppers. Check local recycling guidelines to recycle our packaging!

For more information about Mactac Sustainability commitment please visit the Mactac Graphics website: www.mactacgraphics.eu/en/about-us/sustainable-graphics-solutions



The mark of responsible forestry
FSC® C004451

©2021 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.

All Mactac statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Mactac products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Mactac products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>



Mactac Quick Portfolio Guide

Overlaminates Products

(1/2)

Application	Product name	PVC FREE	Caliper (µm)	Front film: Color and Finish						Adhesive	Liner	Durability**	Conformability	Outdoor application	Fire certification EN 13501-1		
				Clear	Glossy	Matt	Satin	Optically clear	Textured							Permanent	UV inks compatible
Vehicle wrapping																	
Long term application on curved surfaces	LF 10700 CG-UV		30	●	●					●	●	CK	🔄	6 yrs	3D	●	B-s1,d0
	LF 10700 CM-UV		30	●	●	●				●	●	CK	🔄	6 yrs	3D	●	B-s1,d0
	LF 10500 CG		50	●	●		●			●		PET	🔄	5 yrs	2D	●	B-s1,d0
	Permacolor HORIZON TM	🔄	35	●	●					●		CK	🔄	7 yrs	3D	●	na
Curved surfaces																	
Long term application for curved surfaces	LF 9700 CG-UV		80	●	●					●	●	CK	🔄	5 yrs	2D	●	B-s2,d0
	LF 9700 CM-UV		80	●	●	●				●	●	CK	🔄	5 yrs	2D	●	B-s2,d0
	LF 9500 CG		65	●	●					●	●	CK	🔄	4 yrs	2D	●	B-s1,d0
	LF 9500 CM		65	●	●	●				●	●	CK	🔄	4 yrs	2D	●	B-s1,d0
Medium term application for slightly curved surfaces	LF 9300 CG-UV		80	●	●					●	●	CK	🔄	3 yrs	2D	●	B-s1,d0
	LF 9300 CM-UV		80	●	●	●				●	●	CK	🔄	3 yrs	2D	●	B-s1,d0
	LF 9300 CS-UV		80	●	●		●			●	●	CK	🔄	3 yrs	2D	●	B-s1,d0
Flat to slightly curved surfaces																	
Medium term application for slightly curved surfaces	LF 8700 CG-UV		80	●	●					●	●	CK	🔄	3 yrs	1-2D	●	B-s1,d0
	LF 8700 CM-UV		80	●	●	●				●	●	CK	🔄	3 yrs	1-2D	●	B-s1,d0
	LF 8700 CS-UV		80	●	●		●			●	●	CK	🔄	3 yrs	1-2D	●	B-s1,d0
Short term application for flat surfaces	LF 8500 CG		70	●	●					●	●	CK	🔄	2 yrs	1D	●	B-s1,d0
	LF 8500 CM		70	●	●	●				●	●	CK	🔄	2 yrs	1D	●	B-s1,d0

* Forest Council Stewardship (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: C004451).
** For more information please refer to the TB 7.5 Outdoor durability of Mactac Graphics self adhesive films.
*** All Floor Graphics products are EN 13036-4 Anti-slip certified.

Overlaminates Products

(2/2)

Application	Product name	PVC FREE	Caliper (µm)	Front film: Color and Finish						Adhesive	Liner	Durability**	Conformability	Outdoor application	Fire certification EN 13501-1		
				Clear	Glossy	Matt	Satin	Optically clear	Textured							Permanent	UV inks compatible
Floor Graphics***																	
Short term floor application	LF 6302 Floorgraphics		100	●	●					●	●	CK	🔄	2 mths	1D	●	Bfl-s1
	LUV 6300		125	●	●					●	●	CK	🔄	6 mths	1D	●	Bfl-s1
	LUG 6301		100	●	●					●	●	CK	🔄	3 mths	1D	●	Bfl-s1
	LUV 6400	🔄	125	●	●					●	●	CK	🔄	H: 3 yrs/ V: 3 mths	1D	●	Bfl-s1
	FloorGrip		150	●	●					●	●	CK	🔄	H: 1 yr/ V: 3 mths	1D	●	Bfl-s1
	StreetLam		385	●	●		●			●	●	CK	🔄	6 mths	2D+	●	Bfl-s1
Special Laminating films																	
Anti-graffiti application	LUV 7036	🔄	36	●	●			●		●	●	PET	🔄	3 yrs	1D	●	B-s1,d0
	LAG 100	🔄	60	●	●		●			●	●	CK	🔄	3 yrs	2D+	●	B-s1,d0
Anti-graffiti/ photographic	PG 7075	🔄	75	●	●			●		●	●	PET	🔄	3 yrs	1D	●	B-s1,d0
	Photographics		70	●	●					●	●	CK	🔄	4 yrs	2D	●	na
PermaFun Series	Brushed Metal		100	●	●					●	●	CK	🔄	5 yrs	1D	●	B-s1,d0
	Coarse Wood		120	●	●					●	●	CK	🔄	5 yrs	1D	●	C-s1,d0
	Carbon Fibers		150	●	●					●	●	CK	🔄	3 yrs	1D	●	C-s1,d0
Whiteboard application	PG 7034	🔄	30	●	●					●	●	PET	🔄	2 yrs	1D	●	na
Mounting films																	
Mounting films	PP 2011+	🔄	12	●	●					●	●	SC paper	🔄	5 yrs	1D	●	na
	PP 2018+	🔄	12	●	●					●	●	SC paper	🔄	2 yrs	1D	●	na
	PT 2113	🔄	36	●	●					●	●	PET	🔄	3 yrs	1D	●	na

* Forest Council Stewardship (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: C004451).
** For more information please refer to the TB 7.5 Outdoor durability of Mactac Graphics self adhesive films.
*** All Floor Graphics products are EN 13036-4 Anti-slip certified.

Digital Printing Media



JT 10700 WG-BFG XR



JT 9700 WT-BFT Frosted



WW Country Paper



WW 100 Pro

Application	Product name	PVC FREE	Caliper (µm)	Front film: Color and Finish								Adhesive					Liner	Durability**		Conformability	Compatible ink tech.			Outdoor application	Fire certification EN 13501-1	Overlaminates						
				White	Clear	Translucent	Glossy	Matt	Satin	Textured	Perforated	High Tack	Permanent	Removable	Semi-Permanent	Bubble-free		Dot	Grey		Transparent	Black	Type				FSC*	Unprinted	Printed + Laminated	Latex	UV	Solvent
Vehicle wrapping																																
Long term application on curved surfaces	JT 10700 WG-BFG XR		50	●			●							●						PE	●	7 yrs	5 yrs	3D		●	●	●	●	B-s1,d0	LF 10700 UV Series	
	JT 10700 WG-BFG		50	●			●							●						PE	●	7 yrs	5 yrs	3D		●	●	●	●	B-s1,d0	LF 10700 UV Series	
	JT 10500 WG-BFG		55	●			●								●						PE	●	7 yrs	4 yrs	2D		●	●	●	●	B-s1,d0	LF 10500 CG / LF 10700 UV Series
Curved surfaces																																
Long term application on curved surfaces	JT 9700 WG-PG		70	●			●							●						PE	●	7 yrs	5 yrs	2D		●	●	●	●	B-s1,d0	LF 9700 UV Series	
	JT 9700 WG-PT		70	●			●							●						PE	●	7 yrs	5 yrs	2D		●	●	●	●	B-s1,d0		
	JT 9700 WG-BFG		70	●			●							●						PE	●	7 yrs	5 yrs	2D		●	●	●	●	B-s1,d0		
	JT 9700 CG-PT		70		●		●							●						PE	●	7 yrs	5 yrs	2D		●	●	●	●	B-s1,d0		
	JT 9700 CG-BFT		70		●		●							●						PE	●	7 yrs	5 yrs	2D		●	●	●	●	B-s1,d0		
	JT 9700 WT-PT		70	●		●								●						PE	●	7 yrs	5 yrs	2D		●	●	●	●	B-s1,d0		
	JT 9500 WG-PG		65	●			●							●						CK	●	7 yrs	4 yrs	2D		●	●	●	●	B-s1,d0	LF 9500 Series	
	JT 9500 WG-PT		65	●			●							●						CK	●	7 yrs	4 yrs	2D		●	●	●	●	B-s1,d0		
	JT 9500 WG-BFG		65	●			●							●						CK	●	7 yrs	4 yrs	2D		●	●	●	●	B-s1,d0		
	JT 9500 WM-PG		65	●			●		●					●						CK	●	7 yrs	4 yrs	2D		●	●	●	●	B-s1,d0		
	JT 9500 CG-RT		65	●		●		●						●						CK	●	7 yrs	4 yrs	2D		●	●	●	●	B-s1,d0		
	JT 9300 WG-PG		80	●			●							●						PE	●	5 yrs	3 yrs	2D		●	●	●	●	B-s2,d0	LF 9300 UV Series	
JT 9300 WG-PT		80	●			●							●						PE	●	5 yrs	3 yrs	2D		●	●	●	●	B-s2,d0			
JT 9300 WG-RG		80	●			●							●						PE	●	5 yrs	3 yrs	2D		●	●	●	●	B-s2,d0			
JT 9300 WG-BFG		80	●			●							●						PE	●	5 yrs	3 yrs	2D		●	●	●	●	B-s2,d0			
JT 9300 CG-PT		80		●		●							●						PE	●	5 yrs	3 yrs	2D		●	●	●	●	B-s2,d0			
Flat surfaces																																
Medium term application on flat or slightly curved surfaces	JT 8700 WG-PG		90	●			●						●							CK	●	4 yrs	3 yrs	1D		●	●	●	●	B-s2,d0	LF 8700 UV Series	
	JT 8700 WG-RG		90	●			●						●							CK	●	4 yrs	3 yrs	1D		●	●	●	●	B-s2,d0		
	JT 8700 WM-PG		90	●			●		●				●							CK	●	4 yrs	3 yrs	1D		●	●	●	●	B-s2,d0		
	JT 8700 WM-RG		90	●			●		●				●							CK	●	4 yrs	3 yrs	1D		●	●	●	●	B-s2,d0		
	JT 8700 CG-RT		75		●		●						●							CK	●	4 yrs	3 yrs	1D		●	●	●	●	B-s2,d0		
	JT 8700 WT-PT		80	●		●							●							CK	●	4 yrs	2 yrs	1D		●	●	●	●	B-s2,d0		
	JT 8526 P		90	●			●						●							CK	●	4 yrs	2 yrs	1D		●	●	●	●	na	LF 8500 Series	
	JT 8500 WG-PG		95	●			●						●							CK	●	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0		
	JT 8500 WG-PT		95	●			●						●							CK	●	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0		
	JT 8500 WG-RG		95	●			●						●							CK	●	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0		
JT 8500 WG-RT		95	●			●						●							CK	●	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0			
JT 8500 WG-SPB		90	●			●						●							CK	●	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0			
JT 8500 WM-PG		95	●			●		●				●							CK	●	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0			
JT 8500 WM-PT		95	●			●		●				●							CK	●	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0			
JT 8500 WM-RG		95	●			●		●				●							CK	●	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0			
JT 8500 WM-RT		95	●			●		●				●							CK	●	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0			
JT 8500 WM-HTT		95	●			●		●				●							CK	●	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0			
JT 8500 CG-RT		95		●		●						●							CK	●	3 yrs	2 yrs	1D		●	●	●	●	B-s1,d0			
Imagin Easy 209 P		200	●			●						●							CK	●	2 yrs	1 yr	1D		●	●	●	●	na	LF 8700 UV Series		
Dot Series																																
Short term promotional graphics on flat surfaces	JT 8300 WM-RT Dot		120	●			●						●							CK	●	1 yr		1D		●	●	●	●	B-s2,d0		
	JT 8300 CG-RT Dot		120		●		●						●								CK	●	1 yr		1D		●	●	●	●	B-s2,d0	
	JT 8300 WM-RT Dot Floor***		200	●			●						●								CK	●	3 mths	1 mth	1D		●	●	●	●	Bfl-s1	
Floor Graphics***																																
Promotional graphics on floors	StreetRap		70	●			●						●							PE		6 mths	6 mths	2D+		●	●	●	●	Bfl-s1	StreetLam / FloorGrip	
Window Graphics																																
Perforated window films	JT 7300 WG-PT 30		180	●			●						●							PE		1 yr	2 yrs	1D					●	na	LUV 7036 / LF 10500 CG	
	JT 7300 WG-PB 40		180	●			●						●							CK		1 yr	2 yrs	1D					●	B-s2,d0		
	JT 7300 WG-PB 30		150	●			●						●							PE		1 yr	3 yrs	1D					●	na		
	JT 7500 WG-PB 40		180	●			●						●							CK		2 yrs	2 yrs	2D					●	B-s2,d0		
Long term window films	JT 9700 WT-BFT Frosted		80			●		●					●							PE	●	5 yrs		2D					●	na		
	JT 9700 WT-BFT Dusted		80			●		●					●							PE	●	5 yrs		2D					●	na		
Architectural Wall Application																																
Smooth surfaces	WW 309		100	●			●						●							CK	●	4 yrs	3 yrs	1D		●	●	●	●	B-s1,d0	LF 8700 UV Series / LUV 7036 / LAG 100 / LUV 6300 / FloorGrip	
	WW 300		100	●			●						●							CK	●	4 yrs	3 yrs	1D		●	●	●	●	B-s1,d0		
	WW 200		150	●			●						●							PE		1 yr		1D					●	na		
	WW 100 Pro		55	●			●						●							PE		3 yrs	3 yrs	2D		●	●	●	●	B-s1,d0		
	WW Smooth Paper	●	300	●			●						●							CK	●	4 yrs		1D		●	●	●	●	B-s1,d0		
	WW Smooth Textile	●	250	●			●		●				●							CK	●	4 yrs		1D		●	●	●	●	C-s1,d0		
Textured surfaces	WW Canvas		250	●			●						●							CK	●	3 yrs		1D		●	●	●	●	B-s2,d0		
	WW Veneziano		300	●			●						●							CK	●	3 yrs		1D		●	●	●	●	B-s2,d0		
	WW Leather		225	●			●						●							CK	●	3 yrs		1D		●	●	●	●	B-s2,d0		
	WW Linen Paper	●	230	●			●						●							CK	●	4 yrs		1D		●	●	●	●	B-s1,d0		
	WW Country Paper	●	220	●			●						●							CK	●	4 yrs		1D		●	●	●	●	B-s1,d0		
PVC Free																																
Short term application	JT 5425 PUV	●	100	●			●						●							CK	●	2 yrs		1D					●	na	LUV 7036 / LUV 6400	
	JT 5409 RUV	●	50		●		●						●							PET		2 yrs		1D					●	B-s1,d0		

* Forest Council Stewardship (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: C004451).

** For more information please refer to the TB 7.5 Outdoor durability of Mactac Graphics self adhesive films.

*** All Floor Graphics products are EN 13036